

## CENTER MOUNT EVAPORATORS SERIES



Center mount evaporators are designed to be mounted at the center of a walk-in cooler or freezer ceiling, providing optimal airflow and even temperature distribution throughout the space. Available in medium temperature (32–38°F) and low temperature (-10–10°F) models, these units are ideal for spaces where uniform cooling is critical, helping maintain product quality while maximizing storage efficiency. Their design allows for efficient defrosting and easy maintenance.

### Low Temp Features

- ❖ Center mount freezer evaporator with dual airflow.
- ❖ Electric defrost for effective frost control.
- ❖ Designed for consistent freezer performance.
- ❖ Center mount freezer evaporator with balanced airflow.
- ❖ Effective frost control with electric defrosts.
- ❖ Optimized for walk-in freezers.
- ❖ High-capacity freezer evaporator.
- ❖ ECM fans provide strong air throw.
- ❖ Built for demanding freezer applications.

### Medium Temp Features

- ❖ Dual airflow for even temperature distribution.
- ❖ Ideal for square or medium-sized coolers.
- ❖ Rugged construction for commercial use.
- ❖ Balanced dual airflow for uniform cooling.
- ❖ Ideal for small walk-in coolers.
- ❖ Durable construction for daily operation.
- ❖ High-output center mount design.
- ❖ Even temperature distribution across large spaces.
- ❖ Optimized fan configuration for efficiency.
- ❖ Heavy-duty evaporator for high-load coolers.
- ❖ ECM fans for energy savings.
- ❖ Built for continuous commercial operation.
- ❖ Balanced dual airflow for uniform cooling.
- ❖ Ideal for medium-sized walk-in coolers.

Model	Description	Temperature	Defrost Type	Capacity	Refrigerant	Voltage	Airflow	Fan Type
<b>EV-MT-CM-090</b>	Medium Temp Center Mount Evaporator - 9000 BTU	28-40 F	Air Defrost	9000 BTU/hr	R404A / R448A	115/1/60	Dual Flow	PSC
<b>EV-MT-CM-120</b>	Medium Temp Center Mount Evaporator - 12000 BTU	28-40 F	Air Defrost	12000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	PSC
<b>EV-MT-CM-150</b>	Medium Temp Center Mount Evaporator - 15000 BTU	28-40 F	Air Defrost	15000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	PSC
<b>EV-MT-CM-180</b>	Medium Temp Center Mount Evaporator - 18000 BTU	28-40 F	Air Defrost	18000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	PSC
<b>EV-MT-CM-240</b>	Medium Temp Center Mount Evaporator - 24000 BTU	28-40 F	Air Defrost	24000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	ECM
<b>EV-LT-CM-150</b>	Low Temp Center Mount Evaporator - 15000 BTU	-10-10 F	Electric Defrost	15000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	ECM
<b>EV-LT-CM-180</b>	Low Temp Center Mount Evaporator - 18000 BTU	-10-10 F	Electric Defrost	18000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	ECM
<b>EV-LT-CM-240</b>	Low Temp Center Mount Evaporator - 24000 BTU	-10-10 F	Electric Defrost	24000 BTU/hr	R404A / R448A	208-230/1/60	Dual Flow	ECM